

# MiniPCI-WLAN-Card USB Wireless LAN module

## MiniPCI WLAN Module



## Specifications

<b>Chipset</b>	VIA VT6655 Wireless LAN Controller
<b>Bus</b>	Mini-PCI standard compliant
<b>Frequency Band</b>	2400-2483.5MHz (for US, Canada) 2400-2483.5MHz (for Europe) 2400-2497MHz (for Japan)
<b>Operating Channel</b>	IEEE 802.1b, Direct Sequence Spread Spectrum, IEEE 802.11g, Orthogonal Frequency Division Multiplexing 11 Channels (US, Canada) 13 Channels (Europe and Japan)
<b>Driver Support</b>	Windows: 98SE/Me/NT/2000/XP/2003 Ser., Linux (2.4.x/2.6.x), CE (4.2/5.0/6.0) Linux source code available on website
<b>Power consumption</b>	802.11b: 250 mA @ 3.3V, 802.11g: 230mA @ 3.3V Listening: 190mA @ 3.3V
<b>Weight</b>	20g
<b>Board Size</b>	64.7 x 44.6 x 3.8mm
<b>Operating Temperature</b>	0°C ~ +55°C
<b>Compliance Certifications</b>	CE/FCC/Wi-Fi/NCC/Telec/Singapore

## Packing List

- MINI-PCI-WLAN-CARD x1
- WIRELESS-ANTENNA x1 (Optional)
- WIRELESS-CABLE-150MM x1 (Optional)



## Specifications

<b>Chipset</b>	VIA VT6656 Wireless LAN Controller
<b>Bus</b>	USB standard compliant
<b>Frequency Band</b>	2400-2483.5MHz (for US, Canada) 2400-2483.5MHz (for Europe) 2400-2497MHz (for Japan)
<b>Operating Channel</b>	IEEE 802.1b, Direct Sequence Spread Spectrum, IEEE 802.11g, Orthogonal Frequency Division Multiplexing 11 Channels (US, Canada) 13 Channels (Europe and Japan)
<b>Driver Support</b>	Windows: 98SE/Me/NT/2000/XP/2003 Ser., Linux (2.4.x/2.6.x), CE (4.2/5.0/6.0) Linux source code available on website
<b>Power consumption</b>	802.11b: 250 mA @ 3.3V, 802.11g: 230mA @ 3.3V Listening: 190mA @ 3.3V
<b>Weight</b>	10g
<b>Board Size</b>	25 x 60 x 5.9mm
<b>Operating Temperature</b>	0°C ~ +55°C
<b>Compliance Certifications</b>	CE/FCC/Wi-Fi/NCC/Telec/Singapore

## Packing List

- USB-WLAN-MODULE x1
- WIRELESS-CABLE-150MM x1 (Optional)
- WIRELESS-ANTENNA x1 (Optional)
- CABLE-WLAN-30M (2.0) x1 (Optional)
- CABLE-WLAN-30M (2.54) x1 (Optional)
- CABLE-USB-WLAN-30CM x1 (Optional)