HYPER-KBN

PICO-ITX SBC supports AMD® Embedded G-Series SoC with DDR3, DVI-I/LVDS, GbE, USB 3.0, SATA 6Gb/s, Audio and RoHS



Flexible Application
Small size form factor: PICO-ITX

New



Specifications

- SoC
  AMD® Embedded G-Series SoC
  GX-415GA on-board SoC (1.5GHz, Quad-core, 2MB cache, TDP=15W with fan solution)
  GX-210HA on-board SoC (1.0GHz, Dual-core, 1MB cache, TDP=9W with fanless solution)
  GX-420CA on-board SoC (2.0GHz, Quad-core, 2MB cache, TDP=25W with fan solution) (by request)
  GX-217GA on-board SoC (1.65GHz, Dual-core, 1MB cache, TDP=15W with fanless solution) (by request)
- BIOS
  AMI UEFI BIOS
- Memory
  One 204-pin 1600/1333 single-channel DDR3/DDR3L SO-DIMM supported (system max. 8GB)
- Graphics
  GPU frequency 500MHz (Radeon™ HD 8330E) for GX-415GA
  GPU frequency 450MHz (Radeon™ HD 8310E) for GX-210HA
  GPU frequency 600MHz (Radeon™ HD 8400E) for GX-420CA
  GPU frequency 300MHz (Radeon™ HD 8280E) for GX-217GA
  Support for DX11.1, OpenGL 4.1 and OpenCL1.2
  UVD4.2 decode for H.264, MPEG2/4, VC1, MVC
  VCE 2.0 encode for H.264, VCE
- Display Out
  DVI-I (DVI-D up to 1920x1200@60Hz, VGA up to 2048x1536@60Hz)
  18-bit single channel LVDS (up to 1600x900@60Hz)
- Ethernet
  GBE1: Realtek RTL8111E with ASF 2.0 support
- I/O Interfaces
  1 x RS-232 — 1 x SATA 6Gb/s with 5V SATA power connector
  2 x USB 3.0 (on rear I/O) — 2 x USB 2.0 (by pin header)
- Audio
  Realtek AL662 HD codec
  1 x Analog audio by 10-pin (2x5) header
- Front Panel
  1 x 6-pin (1x6) wafer for power LED & HDD LED
  1 x 2-pin (1x2) wafer for power button
  1 x 2-pin (1x2) wafer for power reset button
- LAN LED
  2 x 2 Pin for LAN1 Link LED, LAN2 Link LED
- FAN Connector
  1 x 4-pin system fan connector
- Watchdog Timer
  Software Programmable support 1~255 sec. System reset
- Power Supply
  12V only DC input
  1 x external DC power jack (ø5.5 mm)
  Support AT/ATX mode
- Power Consumption
  +12V@ 1.45A (AMD GX-415GA 1.5GHz CPU with 1333MHz 2GB DDR3 memory)
- Operating Temperature
  0°C ~ 60°C
- Storage Temperature
  -10°C ~ 85°C
- Operating Humidity
  5% ~ 95%, non-condensing
- Dimensions (LxW)
  100mm x 72mm
- Weight
  GW:600g/ NW:250g

Features

1. PICO-ITX form fator with AMD® Embedded G-Series SoC supports DDR3/DDR3L up to 1600MHz memory
2. 12V only single voltage design for AT/ATX power by DC power jack
3. DVI-I and 18-bit singel channel LVDS support for dual displays
4. IEI One Key Recovery solution allows you to create rapid OS backup and recovery

Packing List

1 x HYPER-KBN single board computer
1 x SATA with 5V output cable kit (P/N: 32801-000201-100-RS)
1 x Audio cable (P/N: 32000-072100-RS)
1 x RS-232 cable (P/N: 32200-000049-RS)
1 x Specific heatsink
1 x One key recovery CD
1 x QIG
1 x Utility CD

Ordering Information

Part No.	Description
HYPER-KBN-4151-R10	PICO-ITX SBC with AMD 28nm quad-core GX-415GA 1.5GHz (15W) SoC processor, DDR3 DVI-I/LVDS, GbE, SATA 6Gb/s, USB 3.0, HD Audio and RoHS
HYPER-KBN-2101-R10	PICO-ITX SBC with AMD 28nm dual-core GX-210HA 1.0GHz (9W) SoC processor, DDR3 DVI-I/LVDS, GbE, SATA 6Gb/s, USB 3.0, HD Audio and RoHS
32000-070301-RS	Dual ports USB cable