



Specifications

2009.Q1 Release

Model		ALOHA-W10A	ALOHA-12A
Display	LCD Size	10.2"	12.1"
	Resolution	1024 x 600 (WSVGA)	1024 x 768 (XGA)
	Brightness (cd/m ²)	400	400
	Contrast Ratio	400 : 1	500: 1
	LCD Colors	262 k	262 k
	Viewing Angle (H-V)	140°/110°	160°/160°
Connectors	Rear	1 x USB Type-B Input	
		1 x DVI-D	
		1 x VGA	
	Front Panel	2 x USB Type-A	
		1 x Microphone jack	
		1 x Speaker jack	
Side	2 x USB type-A		
	1 x USB type-A		
Touch Panel		N/A	Optional
Camera and Microphone		300K pixel with digital microphone	
Speakers		AMP 2W +AMP 2W	AMP 1.5W +AMP 1.5W
OSD Control		On-screen display (OSD) controlled by cap-sensor	
Power Input		9V~36V	
Environment	Operating Temperature	0~45°C	
	Humidity	5%~95%RH	
	Housing	Metal	
Physical Properties	Weight	2.5 kg	3.16 kg
	Dimensions (L x W x H) (mm)	280.45 x 241.9 x 39	316.41 x 296.74 x 40.7

Ordering Information

Model		Description
Wide 10.2"	ALOHA-10A- [L] -R10	10.2" All-in-one display console, black color
12.1" Touch panel	ALOHA-12A- [L] /T-R-R10	12.1" Advanced All-in-one touch display console, black color
	ALOHA-12A- [L] -R10	12.1" Advanced All-in-one display console, black color

[L] Language Code-

I :Italian F :French T :Traditional Chinese E :English
S :Spanish J :Japanese R :Russian G :German

Packing List

Item	P/N	Description
USB cable	32000-091700-RS	USB A type male and USB B type male (length: 1.8M)
VGA cable	32000-036200-RS	D-SUB 15P male (length: 1.8M)
Power adapter	63000-FSP0401ADF03A821-RS	90V~264V;12V;40W (length: 1.5M)
Power cord	32000-000002-RS	European power cord (length: 183cm)
Touch pen	XTR104-0002-RS	
User's manual and touch driver CD-ROM		

Options

P/N		Description
DVI	32000-115700-RS	DVI cable (length: 1.8M)
	32000-115800-RS	DVI cable (length: 5M)
	32000-115900-RS	DVI cable (length: 10M)
VGA	32000-036200-RS	VGA cable (length: 1.8M)
	32000-077300-RS	VGA cable (length: 5M)
		VGA cable (length:10M)
USB	32000-091700-RS	USB A type male and USB B type male (length: 1.8M)
	32000-077400-RS	USB A type male and USB B type male (length: 5M)
		USB A type male and USB B type male (length: 10M)